

Project Information

PROJECT NAME		LOCATION	
COMPANY		CONTACT NAME	
PHONE		EMAIL	

WIDTH			
☐ 4' (1.22 m)	☐ 6' (1.83 m)	☐ 8' (2.44 m)	☐ 10' (3.05 m)
☐ 12' (4.27 m)	☐ 14' (4.27 m)	☐ 16' (4.88 m)	

DEPTH			
☐ 4' (1.22 m)	☐ 6' (1.83 m)	☐ 8' (2.44 m)	☐ 10' (3.05 m)
☐ 12' (4.27 m)	☐ 14' (4.27 m)	☐ 16' (4.88 m)	☐ 18' (5.29 m)
☐ 20' (6.10 m)	☐ 22' (6.71 m)	☐ 24' (7.32 m)	☐ Other:

DOORS			
☐ Single ☐ _____ 3068 ☐ _____ 4068	☐ Double ☐ _____ 6068 ☐ _____ 8068	☐ Roll-Up ☐ _____ WIDE OPENING ☐ _____ HIGH OPENING	☐ Sliding ☐ _____ WIDE OPENING ☐ _____ HIGH OPENING
☐ Hardware ☐ SS key locked ball knob (standard) ☐ SS panic hardware ☐ Panic hardware ☐ Three-point hardware	☐ Options ☐ 18-inch x 18-inch polycarbonate door window ☐ Static door vent	☐ Other:	

ELECTRICAL Check if no electrical required ☐ NONE		
CONDUIT		
☐ None	☐ Rigid Schedule 40 PVC ⁺	☐ Rigid Schedule 80 PVC
☐ Galvanized Rigid	☐ PVC Coated Galvanized Rigid	☐ Other:

ELECTRICAL (CONTINUED)

LOAD CENTER

☐ None	☐ Other	Style ☐ Main Lug ☐ Main Breaker
☐ Standard [†] Square D single phase, 125A main lug, NEMA 1, 12 space	Phase ☐ Single ☐ Three	Amps ☐ 60 ☐ 100 ☐ 125
☐ GE single phase, 125 A main lug, thermoplastic NEMA 3R, 4 space	Spaces ☐ 12 ☐ 20 ☐ 24 ☐ 30 ☐ 40 ☐ Other _____	☐ 150 ☐ 200 ☐ Other _____
	NEMA ☐ 1 - Metallic Body ☐ 3R - Metallic Body	Enclosure ☐ 3R - Non-Metallic ☐ 3R - Painted ☐ 4X - Non-Metallic ☐ 4X - Painted Stainless Steel

OUTLETS

☐ None	☐ _____ 20 A GFCI with weather cover [†]
-------------------------------	--

SWITCHES

☐ None	☐ Door activated	☐ HOA
☐ Fan [†]	☐ Light [†]	☐ 3-Way

HVAC Check if no HVAC required ☐ NONE

AIR CONDITIONER

Thru-Wall ☐ 5,000 BtuH Class ☐ 8,000 BtuH Class ☐ 10,000 BtuH Class	Specialty On-Wall ☐ 1,500 BtuH Class ☐ Other (BtuH Class):	Specialty On-Wall ☐ NEMA 4X Painted Steel ☐ NEMA 4X Stainless Steel
Bard [™] High Output On-Wall ☐ 1 Ton ☐ 1.5 Ton ☐ 2 Ton ☐ Other (in tons):	Voltage ☐ 120 VAC ☐ 220 VAC ☐ 480 VAC - 1 Phase	Integral Heat ☐ Heat (in Watts):
		☐ Corrosion Package

HVAC (CONTINUED)

FAN *All fans include fiberglass hood and insect screen*

☐ None

Operation

- ☐ Exhaust
☐ Supply

Standard Construction

- ☐ 242 CFM [7-inch]
☐ 600 CFM [10-inch]
☐ 900 CFM [10-inch]
☐ Other (CFM / inches)
_____ CFM _____ IN

Corrosion Construction

- ☐ 652 CFM [10-inch]
☐ 900 CFM [12-inch]
☐ Other (CFM / inches)
_____ CFM _____ IN

HEATER

☐ None

Standard Construction

- ☐ _____ 1,500 Watt
☐ _____ 2,000 Watt

☐ Heat Lamp

Stainless Steel Construction

- ☐ _____ 500 Watt
☐ _____ 1,500 Watt
☐ _____ 2,250 Watt

Specialty Construction

- ☐ _____ NEMA 4X
Watts:
VAC:
VDC:

SHUTTER

☐ None

Rectangular Fiberglass

- ☐ _____ 10-inch X 10-inch
☐ _____ 12-inch X 12-inch
☐ _____ 16-inch X 16-inch
☐ _____ 18-inch X 18-inch
☐ _____ 20-inch X 20-inch

Round Stainless Steel

- ☐ _____ 4-inch (10.16 cm) [fixed]
☐ _____ 4-inch (10.16 cm) [adjustable]
☐ _____ 6-inch (15.24 cm) [fixed]

Operation

- ☐ _____ Exhaust
☐ _____ Intake

☐ _____ 6-inch round [air operated]

LIGHTING *Check if no lighting required* ☐ NONE

INTERIOR LIGHTING

☐ None	☐ _____ LED	☐ _____ Skylight
-------------------------------	------------------------------------	---

EXTERIOR LIGHTING

☐ _____ Compact LED	☐ _____ Photocell
☐ _____ High pressure sodium	☐ _____ Interior switch
☐ _____ Metal halide	

CUSTOMIZATION

Exterior Color ☐ White ☐ Other (specify RAL below:) _____ RAL	Framed opening ☐ _____ IN ☐ _____ IN
---	--

NOTES / SITE SKETCH